



WATER COOLERS

ON-A-WALL MODELS

Model	50°F Drinking Water 90°F Ambient Air Temp.*		Pre-Cooler	Hot 'N Cold™ Model	115 Volts, 60 Hz			Glass Filter Access. Option	Cabinet Color Option	Net Weight Approx.
	Rated Capacity GPH	Base Rate GPH			Compr. HP	Full Load Amps	Rated Watts			
PLF5M	5.0	2.7	Yes	No	1/12	2.0	155	Yes	Yes	60 lbs.
PLF8M	8.0	8.0	No	No	1/5	4.6	320	Yes	Yes	73 lbs.
PLF8MH†	8.0	8.0	No	Yes	1/5	8.9	820	No	Yes	77 lbs.
PLF14M**	14.0	7.8	Yes	No	1/5	4.6	320	Yes	Yes	76 lbs.
PLF14MH†	14.0	7.8	Yes	Yes	1/5	8.9	820	No	Yes	79 lbs.
PLF16M	16.0	8.8	Yes	No	1/3	5.8	400	Yes	Yes	77 lbs.
PLFM	Fountain Only								Yes	35 lbs.
Semi-Recessed Water Coolers										
PLF8S	8.0	8.0	No	No	1/5	4.6	320	Yes	Yes	71 lbs.
PLF14S	14.0	7.8	Yes	No	1/5	4.6	320	Yes	Yes	77 lbs.
Simulated Semi-Recessed Water Coolers										
PLF8SM	7.8	7.8	No	No	1/5	4.3	330	No	Yes	67 lbs.
PLF14SM	14.0	7.6	Yes	No	1/5	4.3	330	No	Yes	69 lbs.



PLF8M



PLFCMSL fountain to the left of any On-A-Wall model for two-level dispensing of cold drinking water.



PLF8S



PLF8SM

BENEFITS OF THE OASIS® BPE BOTTLE COOLER

Stainless Steel Cooling Reservoir

Handle

- Durable Galvanized Steel
- Makes Cooler Easy to Carry

Best Hot Tank in the Industry

- Automatic Reset
- Adjustable Temperature
- Replaceable Element
- Easy to Clean, Drains in Less than One Minute

Blow Molded Polyethylene Cabinet

- Made In the U.S.A.
- Stylish, Softened Square Shape
- Won't Scratch or Stain Flooring

OASIS® WaterGuard® IV

- Simple and Effective
- Low Profile Gives Clean Look to Cooler
- Effectively Eliminates Spills During Bottle Changes
- Two Reusable Caps Included

Internal Metal Frame Won't Break

Drip Tray

- Same as that used on the Square RR™ for Standardization
- Logo Drip Trays Available for Extra Charge

Plastic Base Available

- Easy to Snap on Accessory
- Color Accent Possible
- Can Hide Scratches on the Cabinet Bottom