

ACID CORE SOLDERS

Part No.	Size	Description
20116	1 lb.	50/50 Acid Core Solder



BAR SOLDERS

Part No.	Size	Description
21305	1-1/4 lb.	50/50 Bar Solder
21307	1-1/4 lb.	50/50 Bar Solder
27805	3 lb.	Wiping Solder

USES & BENEFITS

Solder Alloy	Composition by Weight	Melting Range	Benefits, Uses, Etc.
40/60	An alloy of Tin, Silver, Copper and Bismuth	361°F–460°F	Most common general purpose alloy in the core solders.
50/50	50% Tin—50% Lead	361°F–421°F	Good flow characteristics and low melting point.
60/40	60% tin—40% Lead	361°F–375°F	Low melting point and excellent flow characteristics. (Rosin core, used in electronic applications. Solid wire used in leaded glass work.)
95/5	95% Tin—5% Antimony	450°F–464°F	Lead free high strength alloy exhibits excellent creep resistance. used where frequent and extreme temperature changes and vibrations occur such as refrigeration lines, cooling equipment, etc. Narrow melting range.
silver	An alloy of Tin, Silver, Copper and Bismuth	415°F–455°F	Patented lead free alloy specifically formulated for making joints on copper water lines carrying drinking water.



SILVER LEAD FREE PLUMBING SOLDERS

Part No.	Size	Description
23000	1/2 LB.	Silver Lead Free Solder
23001	1 LB.	Silver Lead Free Solder
23002	5 LB.	Silver Lead Free Solder



95/5 LEAD FREE SOLDERS

Part No.	Size	Description
22004	1/2 lb.	95/5 (95 Tin/5 Ant) Wire
22017	1 lb.	95/5 (95 Tin/5 Ant) Wire



PLUMBER'S ABRASIVE SANDCLOTH



180 OPEN MESH CLOTH



NYLON GRIT PADS



FLAME PROTECTOR

Oatey® PUTTIES, LUBES, SEALS, FLUX, CAULKS AND SEALANT



PLUMBER'S PUTTY

- Stainless fixture setting compound for setting frames, faucets, strainer baskets, etc.
- Stays flexible and will not crack or shrink
- Soft pliable material is easy to work with.
- Not for use on marble or plastic.
- Meets Military Spec. TT-P-1536A.

Part No.	Size
31166	16 oz.
31170	3 lb.
31174	5 lb.



PIPE/GASKET LUBE

- Non-toxic, soft, paste-like material for lubricating bell joint pipe gaskets.
- Will not deteriorate natural or synthetic rubber.
- Will not support bacteria.
- Dissolves in hot water.

Part No.	Size
30599	16 oz.
30600	32 oz.
30601	1 gal.
30605	5 gal.



PIPE SEAL

- Caulking lead substitute for sealing cast iron soil pipe joints.
- Air dry putty compound packs easily and resists shrinkage.
- Forms a hard leakproof seal.
- For use whenever it is impractical to pour molten lead.

Part No.	Size
30614	16 oz.



NO. 5 PASTE FLUX

- Cleans and fluxes at the same time.
- Effective on all metals except aluminum, magnesium and stainless steel.
- 100% lead free
- Blended to clean surface oxidation.

Part No.	Size
30011	1.7 oz.
30013	4 oz.
30014	8 oz.
30041	16 oz.



NO. 95 TINNING FLUX

- Formulated with the same high quality as No. 5. However, patented Oatey silver solder powder is added to pre-tin the copper pipe.
- Flux can never burn out.
- 100% lead free.
- Excellent for large diameter copper.
- Does not turn copper green.

Part No.	Size
30374	1.7 oz.
30372	8 oz.
30375	16 oz.



NO. 11 LIQUID FLUX

- Formulated with strong cleaning agent.
- Ensures fast and effective soldering operation.
- No need to clean oxidized copper.
- Can be used for HVAC applications.

Part No.	Size
30106	4 oz.



H-20⁵⁰ PASTE FLUX

- Water flushable.
- As thick as No. 5 flux.
- Meets ASTM B-813.

Part No.	Size
30130	1.7 oz.
30131	4 oz.
30132	8 oz.
30133	16 oz.



TUB-N-TILE CAULK

- White, flexible, latex sealant.
- Fills and seals cracks and joints.
- For caulking around showers, tubs, lavatories and sinks.
- Can be used to reset loose tiles.
- Can be painted when dry with either oil base or latex paint.
- Cleans up with soap and water.

Part No.	Size
30240	6 oz.
30241	10 oz.



TUB-N-TILE ULTRA CLEAR SEALANT

- Applies white and dries clear.
- Flexible butyl acrylate formula adheres to porous surfaces such as wood and masonry.
- Flexible material won't crack or peel and adheres tightly.
- Paintable with no offensive odors.
- Cleans up with soap and water

Part No.	Size
30235	6 oz.



SILICONE SEALANT

- Clear and white sealants for high performance sealing.
- Bonds to porcelain, ceramic marble, fiberglass and most metals.
- Remains permanently elastic.
- When fully cured, recognized by USDA for use in meat and poultry plants.
- Meets Fed. Spec. TT-S-00230C Class A & TT-S-001543A Class A, Mil. Spec. 46106A, ASTM C920, FDA Regulation No. 21 CFR 177.2600.
- Withstands temperature from -60°F to 400°F

Part No.	Size
30236	10.3 oz.
30237	10.3 oz.

Oatey® CEMENT



PVC FLEXIBLE CLEAR CEMENT

- Medium-bodied clear cement for use on flexible PVC pipe and rigid fittings. Up to 3" diameter.
- Formulated to withstand pressures and vibrations commonly associated with spa and swimming pool installations.
- Meets manufacturer's rated line pressure for flexible PVC pipe.
- Recommended application temperature 40°F to 100°F.
- Meets ASTM D-2564.

Part No.	Size
30879	32 oz.



CPVC MEDIUM ORANGE CEMENT

- Medium-bodied orange colored cement for use on CPVC pipe and fittings. Up to 6" diameter.
- For C.T.S. (copper tube size) and Sch. 80, potable water pressure pipe.
- Recommended application temperature 40°F to 100°F.
- Meets ASTM F-493

Part No.	Size
31128	4 oz.
31129	8 oz.
31130	16 oz.
31131	32 oz.
31127	Gallon



CLEAR PRIMER—NSF LISTED

- A clear aggressive primer for use on PVC and CPVC pipe and fittings.
- All schedules and all diameters.
- Removes all surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.
- Meets ASTM F-656.

Part No.	Size
30750	4 oz.
30751	8 oz.
30752	16 oz.
30753	32 oz.
30754	Gallon



PURPLE PRIMER/CLEANER

- Purple-tinted all purpose primer/cleaner for PVC and CPVC pipe and fittings.
- Removes surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.
- Less aggressive than clear primer and purple primer.
- Purple tint for verification for code.

Part No.	Size
30780	4 oz.
30783	8 oz.
30796	16 oz.
30806	32 oz.
30768	Gallon




ALL PURPOSE CLEANER FOR ABS, PVC AND CPVC

- Clear cleaner for ABS, PVC and CPVC pipe and fittings
- All schedules and all diameters
- Fast-acting cleaner removes surface dirt, grease and grime
- Flows freely and evaporates quickly
- Apply at temperatures 40°F to 100°F

Part No.	Size
30779	4 oz.
30779D	4 oz.
30782	8 oz.
30782D	8 oz.
30795	16 oz.
30805	32 oz.
30766	Gallon

Oatey® CEMENT



ALL PURPOSE CEMENT

- Medium-bodied milky clear cement for ABS, PVC, or CPVC up to 6" diameter.
- Recommended for pipe and fittings Sch. 40 and Sch. 80, potable water, pressure pipe, gas, conduit and DWV.
- Recommended application temperature 40°F to 100°F
- Meets performance requirements of ASTM D-2564, D-2235, F-493.

Part No.	Size
30818	4 oz.
30821	8 oz.
30834	16 oz.
30847	32 oz.
30848	Gallon



PVC HEAVY DUTY CLEAR CEMENT

- Heavy-bodied clear cement for PVC pipe and fittings. Up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, gas, conduit ad DWV.
- Recommended application temperature 40°F to 100°F
- Thick formula fills gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

Part No.	Size
30850	4 oz.
30863	8 oz.
30876	16 oz.
31008	32 oz.
31011	Gallon



PVC REGULAR CLEAR CEMENT

- Regular-bodied clear cement for use on PVC pipe and fittings. Up to 4" for DWV Sch. 40 and up to 2" for Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, gas, conduit and DWV.
- Sets up quickly.
- Recommended application temperature 40°F to 100°F.
- Meets ASTM D-2564.

Part No.	Size
31012	4 oz.
31013	8 oz.
31014	16 oz.
31015	32 oz.
31016	Gallon



PVC RAIN-R-SHINE® BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings. Up to 6" diameter.
- Very fast-setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, gas, conduit and DWV.
- Both Sch. 40 and Sch. 80
- Pool/Irrigation
- Recommended application temperature 40°F to 100°F.
- No primer needed on non-pressure DWV, where local codes permit.
- Meets ASTM D-2564.

Part No.	Size
30890	4 oz.
30891	8 oz.
30893	16 oz.
30894	32 oz.
30895	Gallon

