



DRYLOK® MASONRY PRODUCTS

Oil Base DRYLOCK®

**Masonry
Waterproofing**
(Ready Mixed)

DRYLOK Masonry Waterproofing is formulated for waterproofing all interior, exterior, above or below grade masonry walls, cinder and concrete blocks, stucco, brick, retaining walls, basements, concrete swimming pools and foundations. No pre-mixing or pre-wetting necessary.

Guaranteed to Stop Water!



- A masonry WATERPROOFER paint
- Ready mixed—tintable
- Use indoors and out, above or below grade
- Contains synthetic rubber and Portland cement
- Withstands water pressure up to four pounds per square inch behind walls
- Apply straight from the can—no pre-mixing or pre-wetting
- Five-year warranty
- Performance conforms to Fed. Spec. TT-P-1411-A

ORDER NUMBERS


<i>Oil Base Waterproofing*</i>	<i>1 Gal. 2/Case</i>	<i>5 Gal. 1/Case</i>
White	20713	20715
Gray	28013	20815
Beige	21013	21015
Blue	27013	27015

Latex Base DRYLOCK®

**Masonry
Waterproofing**
(Ready Mixed)

Latex Base DRYLOK Masonry Waterproofing is a low odor, water clean-up formula for waterproofing all interior, exterior, above or below grade masonry wall, cinder and concrete blocks, stucco, brick, retaining walls, basements, concrete swimming pools and foundations. No pre-mixing or pre-wetting necessary.

Guaranteed to Stop Water!



- New 2 Gallon Size!*
- A masonry WATERPROOFER paint
 - Ready mixed—tintable
 - Low odor—Non-flammable
 - Guaranteed to stop water even under pressure
 - Clean up with soap and water
 - Applies easily with brush and/or roller
 - Complies with all current VOC and/or VOS requirements
 - Five-year warranty

ORDER NUMBERS

<i>Latex Base Waterproofing*</i>	<i>1 Qt. 4/Case</i>	<i>1 Gal. 2/Case</i>	<i>2 Gal. 1/Case</i>	<i>5 Gal. 1/Case</i>
White	27512	27513	27514	27515
Gray	n/a	27613	n/a	27615
Beige	n/a	27713	n/a	27715
Blue	n/a	27813	n/a	27815

DRYLOCK®

Fast Plug®

DRYLOK Fast Plug is a fast setting hydraulic cement. Sets in 3-5 minutes to stop the flow of water—even under pressure—through holes and cracks in masonry. It is also ideal for sealing floor and wall joints and settlement cracks in masonry walls.



- New Packaging!*
- A fast-setting hydraulic cement
 - Stops the flow of water through cracks and holes in masonry surfaces.
 - Mixes easily with water—sets in 5 minutes
 - Use to patch mortar joints, cracks and holes in masonry walls
 - Waterproof
 - Ideal for use with DRYLOK Masonry Walls

ORDER NUMBERS

<i>Fast Plug</i>	<i>1-1/2 Lbs.</i>	<i>3 Lb.</i>	<i>10 Lb.</i>	<i>50 Lb.</i>
------------------	-------------------	--------------	---------------	---------------

UGL® CAULKS AND SEALANTS

25-Year Lasticaulk®

UGL 25-Year Lasticaulk is a paintable, non-staining, acrylic latex-silicone compound designed for greater-adhesion and longer life. Lasticaulk guns easily and forms a durable, elastic, water-tight seal that resists weather and mildew. Lasticaulk helps protect your home against drafts and moisture. It bonds perfectly to wood, masonry, metal, tile or glass.



- Paintable
- Bonds perfectly to wood, masonry, metal, tile or glass
- Acrylic latex—silicone formula
- Long life and flexibility
- Easy gunning—water clean-up—interior/exterior use
- Resistant to water, weather, mildew
- Superior adhesive properties
- Warranted for 25 years
- Meets ASTM Spec. C-834-76

ORDER NUMBERS

25-Year Lasticaulk	10.5 Fl Oz. Cartridge 10/Case
White	33307
Almond	33607
Brown	33707
Gray	33807
Clear	33407

Nudeck® Roof Cement

Nudeck Roof Cement is a special Wet/Dry Formula designed for cementing and waterproofing chimney and dormer flashings, valley joints and all types of roof seams. Nudeck Plastic Roof Cement remains resilient for years. Contains no coal tar or other adulterants.



New Packaging!

- For cementing and waterproofing chimney, dormer flashing, valley joints and all types of roof seams
- Remains pliable and resilient for years
- May be used on wet or dry surfaces

ORDER NUMBER

Nudeck Roof Cement	10.5 Fl. Oz. Cartridge 10/Case 31907

TEMPROOF®

Furnace Cement

UGL TEMPROOF Furnace Cement is an all-purpose, high-temperature silicate cement for making minor repairs to stoves, furnaces and chimneys. Formulated to withstand temperatures up to 2000°F, UGL TEMPROOF Furnace Cement can be used wherever an adhesive is needed to withstand high heat. It provides excellent bonding to both masonry and metal for use with firebrick and steel or cast iron stoves.



Acrylic Latex Caulk

UGL Acrylic Latex Caulk is an all-purpose acrylic-siliconized compound for use under latex paint or other types of paint. Needs no priming, will not stain or bleed. Ideal for interior or exterior use.



- Paintable, use under both latex and oil base paint
- Easy gunning, interior/exterior caulk
- Fortified with silicone
- Needs no priming, non-staining and non-bleeding
- Remains flexible year round (0-180°F)
- Cleans up with water
- Meets ASTM Spec. C-834-76

ORDER NUMBER

Acrylic Latex Caulk	10.5 Fl. Oz. Cartridge 10/Case
White	30207

Tub & Tile Caulk

UGL Tub & Tile Caulk is a mildew resistant, non-staining compound that stays white and provides excellent adhesion to most building materials. Waterproofs around tubs, sinks and showers. Quick, easy clean-up with water.



- Use on tubs, showers, sinks and setting plastic, metal and ceramic tiles
- Latex compound fortified with silicone
- Waterproof and mildew resistant
- Easy to use—dries in 30 minutes
- Merchandising display available for 6 oz. tubes
- Available in white only

ORDER NUMBER

Tub & Tile Caulk	6 Oz. Tube 12/Case 30705
White	

- All-purpose, high-temperature silicate cement
- Withstands heat up to 2000°F
- Provides excellent bonding to masonry and metal
- Use with firebrick, steel and cast iron stoves

ORDER NUMBERS

Furnace Cement*	1/2 Pt. 6/Case 10006	1 Pt. 6/Case 10011	1 Qt. 6/Case 10012